



MANNOL Agro Formula H 7859

A special high-quality synthetic-based engine oil for 2-stroke Husqvarna engines. It is suitable for the lubrication by a pre-mixed blend and an automatic mixing in an engine intake.

Product properties:

- A special additive package and a synthetic base ensure a stable operation of an engine in any operating conditions, including high temperatures and loads, as well as when using a low-quality fuel, they prevent the formation of carbon deposits, lacquer and soot on pistons, plugs and valves, prevent piston rings from sticking thus extending the service life of the engine;
- Smokeless combustion;
- Special ashless detergent components maintain the excellent cleanliness of the engine parts;
- It instantly forms a highly stable mixture with all types of fuel;
- It has excellent anticorrosion, antiwear and antifriction properties.

It is designed for use in all types of 2-stroke engines of gardening equipment: lawn-mowers, grass-trimmers, power cultivators, chain and circular saws, special forestry and construction equipment, etc.

The fuel-oil mixture ratio recommended by engine manufacturers must be observed. In the absence of it – the recommended ratio is 1:50.

Comply with the manufacturer's instructions provided in the user's manual of the engine!

It is dyed green for the visual control of the oil in the mixture.

Specifications

API TC

JASO FB

Recommendation

HUSQVARNA

PACKAGING

	MN7859-1PET		
1000L	MN7859-IBC	Pallet tank	
208L	MN7859-DR	Drum	
60L	MN7859-60	Drum	
20L	MN7859-20	Plastic	
	MN7859-012PET		
1L DS	MN7859-1DS		

