



## MANNOL Agro Formula H 7859

A special high-quality synthetic-based engine oil for 2-stroke Husqvarna engines. It is suitable for the lubrication by a pre-mixed blend and an automatic mixing in an engine intake.

Product properties:

- A special additive package and a synthetic base ensure a stable operation of an engine in any operating conditions, including high temperatures and loads, as well as when using a low-quality fuel, they prevent the formation of carbon deposits, lacquer and soot on pistons, plugs and valves, prevent piston rings from sticking thus extending the service life of the engine;
- Smokeless combustion;
- Special ashless detergent components maintain the excellent cleanliness of the engine parts;
- It instantly forms a highly stable mixture with all types of fuel;
- It has excellent anticorrosion, antiwear and antifriction properties.

It is designed for use in all types of 2-stroke engines of gardening equipment: lawn-mowers, grass-trimmers, power cultivators, chain and circular saws, special forestry and construction equipment, etc.

The fuel-oil mixture ratio recommended by engine manufacturers must be observed. In the absence of it – the recommended ratio is 1:50.

Comply with the manufacturer's instructions provided in the user's manual of the engine!

It is dyed green for the visual control of the oil in the mixture.

### Specifications

API TC

JASO FB

### Recommendation

HUSQVARNA

### PACKAGING

	MN7859-1		
1000L	MN7859-IBC	Pallet tank	
208L	MN7859-DR	Drum	
60L	MN7859-60	Drum	
20L	MN7859-20	Plastic	
	MN7859-012PET		
1L DS	MN7859-1DS		

