



## MANNOL Compressor Oil ISO 100 2902

Highly-purified paraffin low-ash mineral compressor oil with an extended replacement age. It ensures a stable and continuous operation of the equipment throughout the entire operation period.

Product properties:

- It contains antifriction, antiwear, anti-oxidising, anticorrosion and antifoaming additives;
- An excellent thermal stability;
- Great antiwear properties;
- An exceptional resistance to oxidation and ageing;
- A minimal formation of deposits and sediments: it guarantees the cleanliness of all mechanical parts, prevents the risk of fire or explosion;
- It has excellent anticorrosion and antifoaming properties and a low evaporation capacity;
- It is recommended for use at ambient temperatures of -25 °C and up;
- It has excellent cooling properties;
- It is compatible with all sealing materials;
- The replacement period up to 4,000 running hours.

Application: All types of air piston-type (easy, moderate and heavy operating modes) and air rotary (easy and moderate operating modes) compressors with the outlet air temperature up to 220 °C.

It can be used in hydraulic systems as a low-ash oil.

In order to properly use it, thoroughly read the user's manual of the equipment.

## Recommendation

ISO Viscosity Grade 100  
DIN 51506 (VBL)  
DIN 51506 (VCL)  
DIN 51506 (VDL)  
DIN 51515-1 (L-TD)  
DIN 51515-2 (TG)  
DIN 51517-2  
DIN 51524-1  
DIN 51524-2  
ISO DP 6521 (DAA, DAB, DAH, DAG)  
AFNOR FRANCE NF E 48-603  
BSI GB BS 489  
CEGB 207001  
MIL L 17672 D  
VDMA 24568  
BROWN BOVERI HTGD 90117  
GE GEK 32568 A  
GE GEK 32568 C  
MAG CINCINNATI P-38  
MAG CINCINNATI P-55  
MAG CINCINNATI P-54  
MAG CINCINNATI P-57  
MAG CINCINNATI P-62  
MITSUBISHI E00-87182  
PARKER DENISON HF-0  
SIEMENS TLV 9013  
US STEEL 120

## PACKAGING

1L	MN2902-1	Plastic	20 pcs/box
208L	MN2902-DR	Drum	
60L	MN2902-60	Drum	
20L	MN2902-20	Plastic	
10L	MN2902-10	Plastic	