



MANNOL Extra Gear Oil 75W-90 GL-4/GL-5 LS 8103

A universal last-generation energy-conserving all-season synthetic gear oil for all types of manual transmissions. It is recommended for use in all types of synchronized manual transmissions (including heavy-duty), in differentials (including LS with excessive friction), steering equipment and other transmission parts where an excessive pressure and impact load is encountered and in which the use of standards GL-4 and/or GL-5 is prescribed.

Product properties:

- The unique synthetic base of the highest quality with ideal viscosity in a wide range of temperatures in combination with a latest-generation additive package ensures superior antifriction properties thus ensuring a significant fuel economy and smooth transmission shift;
- Due to its unique composition, it ensures excellent antiwear and anti-scuffing properties that significantly extend the expected life of the technical equipment in all, even the most extreme, modes of operation in a wide range of ambient temperatures. The oil film has an enhanced resistance to increased pressure. It prevents differentials from jamming and reduces piston wear;
- It has superior low-temperature properties that ensure an easy starting, reliable lubrication, as well as an easy and precise transmission shift at any ambient temperatures (up to -40 °C) and in any operating conditions;
- It has an enhanced thermal-oxidative stability and resistance to the thermal degradation thus allowing increasing the time between oil changes and reducing equipment maintenance costs – up to 800 thousand km/3 years (under operation in highway conditions), and in manual transmissions up to 97,500 shift cycles;
- It effectively protects from lacquering and synchronizer ring clogging;
- It protects metal parts from corrosion;
- It is compatible with sealing materials, prevents them from swelling, hardening and shrinking that allows reducing the costs for spare parts;

It is recommended for use in manual transmissions of passenger cars and heavy-load manual transmissions of highway (freight trucks, buses, etc.), off-road (construction, mining, agricultural) and special vehicles produced by European, American and Asian manufacturers in which the required level of service characteristics is GL-4 and/or GL-5.

Comply with the manufacturer's instructions provided in the user's manual.

Specifications

SAE 75W-90

SAE 75W-90

Recommendation

API GL-4

API GL-4

API GL-5 LS (Limited Slip)

API GL-5 LS (Limited Slip)

MACK GO-J

MACK GO-J

MACK GO-J Plus

MACK GO-J Plus

MAN 342 Type M1

MAN 342 Type M1

MAN 342 Type M2

MAN 342 Type M2

MAN 342 Type M3

MAN 342 Type M3

SCANIA STO 1:0

SCANIA STO 1:0

PACKAGING

1L	MN8103-1	Plastic	20 pcs/box
1000L	MN8103NF-IBC	Pallet tank	
1000L	MN8103-IBC	Pallet tank	
208L	MN8103-DR	Drum	
60L	MN8103-60	Drum	
20L	MN8103-20	Plastic	
10L	MN8103-10	Plastic	
4L	MN8103-4	Plastic	4 pcs/box