



## MANNOL For Chinese Cars 5W-30 7924

Synthetic engine oil of medium viscosity for modern petrol and diesel engines of passenger cars with direct and multi point fuel injection, turbocharged and non-turbocharged. Developed in accordance with the requirements of Chinese car manufacturers.

Product properties:

- Improved fuel efficiency thanks to high-quality base oil and optimum anti-friction properties;
- A highly effective additive package and the synthetic base provide fast oil flow to all engine components and separate parts, which ensures a confident cold start in the harshest conditions, thus significantly reducing engine starting wear. Thanks to a stable thickener, it has a stable and high viscosity index, which provides engine protection at all operating modes and at all ambient temperatures. Effectively resists thickening;
- Thanks to its excellent detergent-dispersing properties and highest thermal-oxidising stability, it effectively fights all kinds of deposits and keeps engine parts and turbochargers clean throughout the entire oil change interval. Helps to remove previously formed deposits;
- A highly effective additive package and a low-viscosity synthetic base provide excellent anti-wear properties due to the exceptional stability of the oil film, which, combined with excellent pumpability, considerably extends engine life even in "Start-stop" driving modes. Effectively protects the timing chain from wear. Increases engine life;
- For turbocharged direct injection engines, the unique oil formulation completely prevents LSPI (Low Speed Pre-Ignition);
- Neutral to seal materials;
- Effectively resists aeration and foaming to ensure flawless operation of the hydraulic tappets in all operating modes;
- Compatible with the latest exhaust gas neutralisation systems. Reduces exhaust gas emissions;
- Has low evaporation rate, which reduces operating consumption;
- Used in Long Life and conventional engines.

Designed for all petrol and diesel engines in passenger cars, light off-road vehicles, vans and light trucks, as well as SUVs and light commercial vehicles where API SP/ILSAC GF-6A/GM Dexos 1 Gen3 and lower performance levels of this viscosity grade are required.

Recommended for vehicles: BYD, CHANGAN, CHERY, EXEED, GAC, GEELY, HAVAL, JAECOO, JETOUR, LIFAN, OMODA, SAIC, TANK.

### Specifications

SAE 5W-30

API SP

API SN (RC)

ILSAC GF-6A

GM Dexos 1 Gen3

CHRYSLER MS6395

FORD WSS-M2C961-A1

FORD WSS-M2C946-B1

### Recommendation

SAIC

Geely

BYD

Changan

GAC

Haval

Chery

Jetour

### PACKAGING

	MN7924-5		
	MN7924-20		
	MN7924-4		
	MN7924-1		